



Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	Wt. (Kg)
	d	D	B	N			
				Dynamic	Static		
7000	10.000	26.000	8.000	4185	1863	35100	0.023
7001	12.000	28.000	8.000	4545	2214	31500	0.025
7002	15.000	32.000	9.000	5220	2835	27900	0.035
7003	17.000	35.000	10.000	6435	3465	25200	0.046
7004	20.000	42.000	12.000	8730	5040	22500	0.080
7005	25.000	47.000	12.000	9630	6165	18900	0.093
7006	30.000	55.000	13.000	12510	8505	16200	0.135
7007	35.000	62.000	14.000	15750	11340	14400	0.180
7008	40.000	68.000	15.000	16920	13140	12600	0.222
7009	45.000	75.000	16.000	20070	15930	11700	0.282
7010	50.000	80.000	16.000	21330	18090	9900	0.306
7011	55.000	90.000	18.000	27900	23670	9900	0.447
7012	60.000	95.000	18.000	28800	25290	8640	0.478
7013	65.000	100.000	18.000	30150	28350	8100	0.509
7014	70.000	110.000	20.000	38250	35550	7470	0.705
7015	75.000	115.000	20.000	39150	37350	7020	0.745
7016	80.000	125.000	22.000	48150	45450	6570	0.994
7017	85.000	130.000	22.000	49050	48150	6210	1.040
7018	90.000	140.000	24.000	58500	57150	5850	1.350
7019	95.000	145.000	24.000	60300	60300	5490	1.410
7020	100.000	150.000	24.000	61650	63450	5220	1.470
7022	110.000	170.000	28.000	82800	83700	4770	2.300
7024	120.000	180.000	28.000	84150	88650	4320	2.470
7026	130.000	200.000	33.000	105300	112500	3960	3.730
7028	140.000	210.000	33.000	108000	119700	3690	3.960
7030	150.000	225.000	35.000	123300	138600	3420	4.820

KG®

***Note:**

- Mentioned speed ratings are with oil lubrication. For grease lubrication, please use 75% of the indicated values.



***Note:**
 • Mentioned speed ratings are with oil lubrication.
 For grease lubrication, please use 75% of the indicated values.


Single Row Series : 72

107


Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	Wt. (Kg)
	d	D	B	N			
				Dynamic	Static		
7200	10.000	30.000	9.000	4905	2466	33300	0.029
7201	12.000	32.000	10.000	6435	3140	29700	0.035
7202	15.000	35.000	11.000	8145	4230	26100	0.046
7203	17.000	40.000	12.000	10800	5940	23400	0.064
7204	20.000	47.000	14.000	13050	7560	20700	0.100
7205	25.000	52.000	15.000	14580	9270	17100	0.125
7206	30.000	62.000	16.000	20250	13320	14400	0.193
7207	35.000	72.000	17.000	26730	18090	12600	0.281
7208	40.000	80.000	18.000	31950	22590	11700	0.355
7209	45.000	85.000	19.000	35550	25830	10800	0.404
7210	50.000	90.000	20.000	37350	28350	9000	0.457
7211	55.000	100.000	21.000	45900	35550	8550	0.600
7212	60.000	110.000	22.000	55350	44100	7920	0.765
7213	65.000	120.000	23.000	63450	52200	7290	0.962
7214	70.000	125.000	24.000	68850	57150	6840	1.090
7215	75.000	130.000	25.000	71100	61650	6390	1.170
7216	80.000	140.000	26.000	80100	68400	5940	1.390
7217	85.000	150.000	28.000	89550	79650	5580	1.780
7218	90.000	160.000	30.000	106200	92700	5310	2.180
7219	95.000	170.000	32.000	119700	106200	4950	2.670
7220	100.000	180.000	34.000	129600	113400	4680	3.200
7221	105.000	190.000	36.000	141300	127800	4500	3.790
7222	110.000	200.000	38.000	153000	142200	4230	4.450
7224	120.000	215.000	40.000	164700	159300	3870	6.260
7226	130.000	230.000	40.000	176400	178200	3600	7.150
7228	140.000	250.000	42.000	182700	193500	3240	8.780
7230	150.000	270.000	45.000	208800	233100	3060	11.000

Angular Contact Ball Bearings AC

Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	WL (Kg)
	d	D	B	N			
				Dynamic	Static		
7300	10.000	35.000	11.000	9090	4455	30600	0.040
7301	12.000	37.000	12.000	10080	4725	27000	0.044
7302	15.000	42.000	13.000	12150	6480	23400	0.055
7303	17.000	47.000	14.000	14310	7785	21600	0.107
7304	20.000	52.000	15.000	16830	9360	18900	0.138
7305	25.000	62.000	17.000	23760	14220	15300	0.230
7306	30.000	72.000	19.000	30150	20070	13500	0.345
7307	35.000	80.000	21.000	36000	23670	11700	0.462
7308	40.000	90.000	23.000	44100	29700	10800	0.625
7309	45.000	100.000	25.000	57150	39150	9000	0.837
7310	50.000	110.000	27.000	66600	46800	8460	1.090
7311	55.000	120.000	29.000	77400	55350	7740	1.390
7312	60.000	130.000	31.000	88200	64350	7110	1.740
7313	65.000	140.000	33.000	99900	73800	6570	2.110
7314	70.000	150.000	35.000	112500	84150	6120	2.560
7315	75.000	160.000	37.000	122400	95400	5670	3.070
7316	80.000	170.000	39.000	132300	107100	5310	3.650
7317	85.000	180.000	41.000	143100	119700	5040	4.340
7318	90.000	190.000	43.000	153900	132300	4770	5.060
7319	95.000	200.000	45.000	164700	145800	4500	5.890
7320	100.000	215.000	47.000	186300	117300	4230	7.180
7321	105.000	225.000	48.000	198000	189000	4050	8.200
7322	110.000	240.000	50.000	221400	221400	3870	9.600
7324	120.000	260.000	55.000	221400	226800	3510	14.700
7326	130.000	280.000	58.000	245700	263700	3240	17.600
7328	140.000	300.000	62.000	270000	301500	2970	21.500
7330	150.000	320.000	65.000	297000	342000	2790	25.100



***Note:**
 • Mentioned speed ratings are with oil lubrication.
 For grease lubrication, please use 75% of the indicated values.



***Note:**
 • Mentioned speed ratings are with oil lubrication.
 For grease lubrication, please use 75% of the indicated values.


Single Row Series : 79

109

Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	WL (Kg)
	d	D	B	N			
				Dynamic	Static		
7905	25.000	42.000	9.000	6435	4455	19800	0.050
7906	30.000	47.000	9.000	6795	5175	17100	0.058
7907	35.000	55.000	10.000	10800	7965	15300	0.088
7908	40.000	62.000	12.000	11430	9180	13500	0.130
7909	45.000	68.000	12.000	14130	11610	12600	0.150
7910	50.000	72.000	12.000	14940	13050	10800	0.157
7911	55.000	80.000	13.000	15570	14490	9900	0.214
7912	60.000	85.000	13.000	16290	15660	9000	0.230
7913	65.000	90.000	13.000	16470	16200	8640	0.245
7914	70.000	100.000	16.000	23580	23580	8100	0.397
7915	75.000	105.000	16.000	23850	24390	7560	0.420
7916	80.000	110.000	16.000	24210	25200	7020	0.444
7917	85.000	120.000	18.000	32400	34200	6660	0.628
7918	90.000	125.000	18.000	32850	35550	6300	0.658
7919	95.000	130.000	18.000	33300	36450	5940	0.688
7920	100.000	140.000	20.000	43200	47250	5580	0.934
7921	105.000	145.000	20.000	43650	49050	5310	0.972
7922	110.000	150.000	20.000	44550	50400	5130	1.010
7924	120.000	165.000	22.000	54900	62550	4680	1.660
7926	130.000	180.000	24.000	67500	78750	4230	1.820
7928	140.000	190.000	24.000	67950	81000	3960	1.940
7930	150.000	210.000	28.000	87750	105300	3690	2.960

Angular Contact Ball Bearings AC


Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	Wt. (Kg)
	d	D	B	N			
				Dynamic	Static		
QJ203	17.000	40.000	12.000	14310	9540	17100	0.082
QJ205	25.000	52.000	15.000	22590	18000	12600	0.160
QJ206	30.000	62.000	16.000	31590	25650	10800	0.240
QJ207	35.000	72.000	17.000	41580	35100	9000	0.350
QJ208	40.000	80.000	18.000	47430	40500	8100	0.450
QJ209	45.000	85.000	19.000	52650	45900	7650	0.520
QJ210	50.000	90.000	20.000	55620	50400	6750	0.590
QJ211	55.000	100.000	21.000	71370	68850	6300	0.770
QJ212	60.000	110.000	22.000	83070	77850	5670	0.990
QJ213	65.000	120.000	23.000	93600	93600	5040	1.200
QJ214	70.000	125.000	24.000	102600	102600	5040	1.300
QJ215	75.000	130.000	25.000	105300	109800	4770	1.450
QJ216	80.000	140.000	26.000	124200	131400	4320	1.850
QJ217	85.000	150.000	28.000	133200	144000	4050	2.250
QJ218	90.000	160.000	30.000	156600	167400	3870	2.750
QJ219	95.000	170.000	32.000	179100	190800	3600	3.350
QJ220	100.000	180.000	34.000	202500	216000	3420	4.050
QJ222	110.000	200.000	38.000	238500	274500	3060	5.600
QJ224	120.000	215.000	40.000	257400	306000	2880	6.950
QJ226	130.000	230.000	40.000	266400	328500	2520	7.750
QJ228	140.000	250.000	42.000	292500	396000	2340	9.850
QJ230	150.000	270.000	45.000	304200	418500	2160	12.500



***Note:**
 • Mentioned speed ratings are with oil lubrication.
 For grease lubrication, please use 75% of the indicated values.



Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	Wt. (Kg)
	d	D	B	N			
				Dynamic	Static		
E4	4.000	16.000	5.000	1485	259	36000	0.005
E5	5.000	16.000	5.000	1485	259	36000	0.004
E6	6.000	21.000	7.000	2241	400	32400	0.011
E7	7.000	22.000	7.000	2241	400	32400	0.013
E8	8.000	24.000	7.000	3105	585	30600	0.014
E9	9.000	28.000	8.000	4095	418	27000	0.022
E10	10.000	28.000	8.000	4095	418	27000	0.021
E11	11.000	32.000	7.000	3960	760	23400	0.029
E12	12.000	32.000	7.000	3960	760	23400	0.028
E13	13.000	30.000	7.000	3960	760	23400	0.021
E15	15.000	35.000	8.000	5220	1035	19800	0.034
BO15	15.000	40.000	10.000	6660	1350	18000	0.055
L17	17.000	40.000	10.000	6660	1350	18000	0.051
BO17	17.000	44.000	11.000	6615	1350	17100	0.080
E19	19.000	40.000	9.000	4545	927	18000	0.049
E20	20.000	47.000	12.000	9900	2142	15300	0.089
L20	20.000	47.000	14.000	9900	2142	15300	0.101


***Note:**

- Mentioned speed ratings are with oil lubrication. For grease lubrication, please use 75% of the indicated values.