


Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	WL (Kg)
	d	D	H	N			
				Dynamic	Static		
29230	150.000	215.000	39.000	306000	1206000	1620	4.560
29232	160.000	225.000	39.000	324000	1314000	1530	4.880
29234	170.000	240.000	42.000	382500	1593000	1440	6.020
29236	180.000	250.000	42.000	405000	1728000	1440	6.270
29238	190.000	270.000	48.000	477000	2007000	1260	8.800
29240	200.000	280.000	48.000	481500	2070000	1260	9.140
29244	220.000	300.000	48.000	499500	2232000	1170	9.940
29248	240.000	340.000	60.000	742500	3240000	990	17.500
29252	260.000	360.000	60.000	783000	3555000	990	18.600
29256	280.000	380.000	60.000	787500	3645000	900	19.800
29260	300.000	420.000	73.000	1071000	4815000	783	30.900
29264	320.000	440.000	73.000	1134000	5220000	756	33.500
29268	340.000	460.000	73.000	1116000	5220000	738	34.400
29272	360.000	500.000	85.000	1359000	6345000	648	50.500
29276	380.000	520.000	85.000	1431000	6885000	630	53.400
29280	400.000	540.000	85.000	1458000	7155000	612	55.800
29284	420.000	580.000	95.000	1890000	9360000	558	76.600
29288	440.000	600.000	95.000	1935000	9810000	540	79.600
29292	460.000	620.000	95.000	1935000	9900000	531	82.800
29296	480.000	650.000	103.000	2160000	10800000	495	98.600
292/500	500.000	670.000	103.000	2286000	11700000	477	102.000

KG®


***Note:**

- Mentioned speed ratings are with oil lubrication. For grease lubrication, please use 75% of the indicated values.



Series : **293**

225



***Note:**
 • Mentioned speed ratings are with oil lubrication.
 For grease lubrication, please use 75% of the indicated values.


Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	Wt. (Kg)
	d	D	H	N			
				Dynamic	Static		
29317	85.000	150.000	39.000	238500	738000	2070	2.940
29318	90.000	155.000	39.000	256500	823500	2070	3.080
29320	100.000	170.000	42.000	310500	1044000	1890	3.940
29322	110.000	190.000	48.000	400500	1350000	1620	5.780
29324	120.000	210.000	54.000	481500	1593000	1440	7.920
29326	130.000	225.000	58.000	553500	1890000	1350	9.760
29328	140.000	240.000	60.000	616500	2124000	1260	11.400
29330	150.000	250.000	60.000	607500	2151000	1260	12.000
29332	160.000	270.000	67.000	738000	2574000	1170	15.900
29334	170.000	280.000	67.000	769500	2745000	1080	16.600
29336	180.000	300.000	73.000	895500	3240000	990	21.200
29338	190.000	320.000	78.000	1035000	3825000	990	26.000
29340	200.000	340.000	85.000	1152000	4140000	882	31.900
29344	220.000	360.000	85.000	1251000	4680000	846	34.500
29348	240.000	380.000	85.000	1242000	4725000	819	36.600
29352	260.000	420.000	95.000	1539000	6120000	729	52.000
29356	280.000	440.000	95.000	1620000	6525000	711	54.600
29360	300.000	480.000	109.000	1926000	7425000	630	75.800

Spherical Roller Thrust Bearings

TH

Bearing No.	Dimensions in mm			Basic Load Ratings		RPM*	Wt. (Kg)
	d	D	H	N			
				Dynamic	Static		
29412	60.000	130.000	42.000	254700	724500	2340	2.780
29413	65.000	140.000	45.000	297000	850500	2160	3.440
29414	70.000	150.000	48.000	328500	936000	1980	4.190
29415	75.000	160.000	51.000	373500	1071000	1890	5.070
29416	80.000	170.000	54.000	414000	1242000	1710	6.090
29417	85.000	180.000	58.000	441000	1332000	1620	7.200
29418	90.000	190.000	60.000	490500	1512000	1530	8.380
29420	100.000	210.000	67.000	616500	1917000	1350	11.500
29422	110.000	230.000	73.000	760500	2358000	1260	15.000
29424	120.000	250.000	78.000	877500	2745000	1170	18.600
29426	130.000	270.000	85.000	972000	3195000	1080	23.700
29428	140.000	280.000	85.000	999000	3375000	1080	25.200
29430	150.000	300.000	90.000	1152000	3915000	990	30.500
29432	160.000	320.000	95.000	1350000	4635000	900	37.000
29434	170.000	340.000	103.000	1494000	5175000	846	45.000
29436	180.000	360.000	109.000	1656000	5580000	801	52.900
29438	190.000	380.000	115.000	1809000	6120000	756	62.000
29440	200.000	400.000	122.000	2007000	6885000	711	73.300
29444	220.000	420.000	122.000	2592000	8685000	675	75.000
29448	240.000	440.000	122.000	2691000	9180000	675	80.000
29452	260.000	480.000	132.000	3159000	11610000	603	105.000
29456	280.000	520.000	145.000	3879000	13770000	567	135.000
29460	300.000	540.000	145.000	3933000	14940000	540	140.000
29464	320.000	580.000	155.000	4455000	17100000	504	175.000
29468	340.000	620.000	170.000	5175000	20160000	450	220.000
29472	360.000	640.000	170.000	4815000	19080000	450	230.000
29476	380.000	670.000	175.000	5283000	21600000	432	260.000
29480	400.000	710.000	185.000	5904000	23850000	405	310.000

KG®



*Note:

- Mentioned speed ratings are with oil lubrication. For grease lubrication, please use 75% of the indicated values.